

Material Safety Sheet Data May be used to comply with OSHA's Hazard Communication Standard. 29 CFR 1910.1200. Standard must be consulted for specific requirements.	U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072
IDENTITY (As Used on Label and List) AMERSEAL PREMIUM HEAVY DUTY TIRE SEALANT	

Section I

Manufacturer's Name AMERICAN SEALANTS COMPANY, INC.	Emergency telephone Number (785) 632-2322
Address PO BOX 15	Telephone Number for Information (785) 632-2322
CITY CENTER, KANSAS 67432-0015	Date Prepared January 1, 2004

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name (s))	OSHA PEL	ACGIH TLV	Other Limits	% (optional)
ETHYLENE GLYCOL CAS #107-21-1	50-ppm	50-ppm		Option 48.00%

Section III – Physical/Chemical Characteristics

Boiling Point ABOVE _____	250-F	Specific Gravity (H₂O = 1)	1.08
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (AIR =1)	N/A	Evaporation Rate (Butyl Acetate =1)	Very Low 72
Solubility in Water TOTALLY EMULSIFIABLE. SOLIDIFICATION TEMPERATURE UNDER -45-F			
Appearance and Odor VISCOUS WHITE LIQUID, SLIGHTLY AMMONIACAL			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) NONE DETECTED	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media WATER FOG, CARBON DIOXIDE OR DRY CHEMICAL			
Special Fire Fighting Procedures NONE			
Unusual Fire and Explosion Hazards NONE			